



Installation Instructions

DO NOT USE dB3/Lite TO SURROUND OR ENCLOSE ANY LIGHT FIXTURES

CUT dB3/Lite BACK A MINIMUM OF 24" AWAY FROM ANY CANNED LIGHTS

Preparation

1. Typically installed after framing, insulation, and electrical is complete. Insulation should be used in addition for optimal performance.
2. Ensure that all applicable inspections are completed prior to installation of dB3/Lite
3. dB3/Lite may be installed prior to "drying in" the building (prior to installation of windows and doors)
4. Acclimate dB3/Lite for a minimum of 24 hours at temperatures 60°F or greater to reduce material stiffness when handling.
5. Starting in one corner of the room, install dB3/Lite flush with the top of the wall studs, and hang it vertically.
6. Drywall should be installed within 2-4 weeks of dB3/Lite to prevent excessive wear. If longer delays are expected, washers should be installed to securely fasten dB3/Lite. Drywall installation permanently attaches the dB3/Lite to the stud.

Wood Studs

1. Attach dB3/Lite directly to the top of the wood plate using wide-crown 1/2" staples or pan head screws.
2. A fastener should be placed every 12" for dB3 and 6" for dB3 Lite horizontally along the top.
3. Straighten dB3/Lite so that it is flush against the wood studs and apply from the top down.
4. Using staples or pan head screws, attach dB3/Lite to each stud in the center of the stud. Only 1 fastener is required for each vertical stud each 36".
5. Use an exterior fastener pattern, only fastening to the studs where the seam falls.

NOTE: Hammer stapler may be the best way to attach staples through dB3/Lite into stud.

Metal Studs

1. Attach dB3/Lite directly to the metal stud using pan head screws.
2. A screw every 12" is recommended along the top.
3. Straighten dB3/Lite so it is flush against the metal studs.
4. Using drywall screws, attach dB3/Lite to the stud in the middle of the stud. Only 1 fastener is required for each vertical stud.

NOTE: High Walls

- a. Walls higher than 12' shall have dB3 secured with washers along the top to prevent the fastener from pulling through the material. On walls higher than 10' shall have dB3 Lite secured with washers along the top to prevent the fastener from pulling through the material.
- b. Fasteners should also be used on intermediate studs (in addition to exterior studs) every 24" vertically
5. Install dB3/Lite on all required walls.
6. Keep fasteners as flush as possible, since all protrusions will put a dimple into the finished wallboard. Fasteners shall not protrude more than 1/16" from dB3/Lite surface.
7. Tightly butt the side of the next sheet of dB3/Lite to the edge of the attached sheet. Do not overlap seams.
8. Tape all seams with Seam-Seal or equivalent. Ensure that there are no bubbles or wrinkles in the tape. The tape is semi-permanent, and will be permanently sealed in position when drywall is hung.
 - a. If dB3/Lite is installed horizontally or a seam does not fall on a stud, the seams must be taped preferably with Seam Seal tape, which provides a long-lasting attachment.
 - b. If seams fall on the stud, with no gaps >1/8", then no taping is required. Drywall installation will seal the dB3/Lite against the existing studs.
 - c. Commercial alternatives include commercial duct tape.
9. dB3/Lite is easily cut to fit around irregular objects and electrical boxes. The material should be cut around outlets, switches, and junction boxes. Gaps shall be less than 1/8". If greater, they shall be sealed with acoustical caulk.
10. ISO pads (putty pads) should be installed on the back of all electrical boxes.
11. Caulk the bottom plate at the floor line with acoustical sealant.
12. Install drywall per normal technique (ASTM# C840 – Standard Specification for Application and Finishing of Gypsum Board). dB3/Lite will be fastened permanently when the gypsum board is hung.

Storage

dB3/Lite may be stored in wet or dry environment and may be stored outside on construction sites without special tarps or covering. If stored below freezing temperatures, material may require 24-48 hours of acclimation to regain pliability. dB3 is not recommended for permanent exterior installation where exposed directly to ultraviolet radiation (sunlight).

